

NISOTEC 2T



Engine oil for 2T engines



Engine cleanliness



Mineral

NISOTEC 2T is a high-quality mineral oil for the lubrication of small two-stroke engines (up to 50 cm³) with air cooling. It is formulated with modern ashless additives that provide piston, ring and liner wear protection by reducing deposit formation. The fuel mixture should be in accordance with the engine manufacturer's recommendations.

Applications:



- Small two-stroke air-cooled engines for which mineral oils meeting the JASO FC specification are recommended
- Mopeds, snowmobiles, karting vehicles
- Chainsaws, lawnmowers, cultivators, small generators and other garden equipment

Characteristics	Advantages
Modern low-ash additives	Cleaner combustion and less deposits in the combustion zone
Control of deposits in the engine	The formation of sludge and deposits in the engine is prevented, which enables a longer service life of the engine
Good miscibility with fuel	Excellent combustion without the appearance of deposits in the engine

Specification:

- API TC;
- JASO-FC;
- ISO 6743-15 (L-EGC);
- ISO 13738 (L-EGC)

Typical characteristics

Characteristics	Method	NISOTEC 2T
Kinematic viscosity at 100°C, mm ² /s	ISO 3104	8,65
Viscosity Index	ISO 2909	101
Sulfate ash, m/m %	ISO 3987	0,07
Pour Point, °C	ISO 3016	-24
Flash Point (PM), °C	EN ISO 2719	108
Density at 15°C, kg/m ³	EN ISO 3675	879

Health, Safety and Environment

Information on the safe handling, storage and disposal of the product, as well as information on precautionary measures and potential hazards, effects on human health and the environment can be found in the Product Safety Data Sheet (SDS). Store the product in its original packaging protected from atmospheric influences. Shelf life 5 years from the date of manufacture.

Available packaging



0,5L



1L



205L



1000L