

NISOTEC AUTOGAS SAE 15W-40



Engine oil



Mineral



Protection against the formation of high-temperature deposits



Engines powered by liquefied petroleum gas



Engines powered by compressed natural gas



Multigrade

NISOTEC AUTOGAS SAE 15W-40 is a high-quality mineral engine oil intended for gasoline engines that use gasoline or liquefied petroleum gas (LPG) or compressed natural gas (CNG) as fuel. It is formulated to provide good protection against engine valve wear, excellent protection against high temperature deposits while saving fuel. It ensures a long service life of engines of various types and years of vehicles with improved protection in a wide temperature range.

Applications:



- Passenger cars, SUV's, light trucks and vans
- Gasoline engines that use gasoline or liquefied petroleum gas (LPG) or compressed natural gas (CNG) as fuel and require oil according to the API SL specification

Characteristics	Advantages
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Good detergent-dispersant characteristics	It ensures excellent engine cleanliness thanks to an advanced additive package
Excellent thermal and oxidation stability	Helps to resist oil aging allowing extended drain interval protection
Deposit control	Prevents forming of sludge and deposits in the engine, which enables a longer engine life
Stay-in-grade	Keeps protective oil film during the whole drain interval and maintains viscosity grade

Specification:

- API SL/CF
- ACEA A3/B3

Typical characteristics

Characteristics	Method	NISOTEC AUTOGAS SAE 15W-40
SAE Viscosity grade	SAE J300	15W-40
Kinematic viscosity at 100°C, mm ² /s	ISO 3104	14,5
Viscosity Index	ISO 2909	140
Total Base Number TBN, mg KOH/g	ISO 3771	7,0
Pour Point, °C	ISO 3016	-27
Flash Point (COC), °C	EN ISO 2592	225
Density at 15°C, kg/m ³	EN ISO 3675	880

Health, Safety and Environment

Information on the safe handling, storage and disposal of the product, as well as information on precautionary measures and potential hazards, effects on human health and the environment can be found in the Product Safety Data Sheet (SDS). Store the product in its original packaging protected from atmospheric influences. Shelf life 5 years from the date of manufacture.

Available packaging



1L



4L



60L



205L



1000L