

NISOTEC AUTOLINE PS SAE 10W-40



Engine oil



Semi-synthetic



Protection against the formation of high-temperature deposits



Gasoline and diesel engines



Engine cleanliness



Multigrade

NISOTEC AUTOLINE PS SAE 10W-40 is a high-quality semi-synthetic engine oil, intended for modern gasoline and diesel engines, with direct fuel injection, with catalysts and turbochargers. Formulated to provide better protection against high temperature deposits, improved sludge and deposit control, and better seal compatibility. It ensures a long service life of engines of various types and years of vehicles, as well as greater economy in fuel consumption, better protection of the turbocharger and lower emission of harmful gases.

Applications:



- Passenger cars, SUV's, light commercial vehicles and vans
- Modern gasoline and diesel engines that work in normal and difficult conditions of exploitation
- Turbocharged and engines with direct and indirect injection

| Characteristics | Advantages |
|---|---|
| Multi-purpose application | High quality formulation suitable for a wide range of vehicle engines |
| Wear protection | A permanent oil film provides protection against wear in all operating conditions, which enables a long service engine life |
| Good detergent-dispersant characteristics | It ensures excellent engine cleanliness thanks to an advanced additive package |
| Excellent thermal and oxidation stability | It ensures the oil's resistance to aging and thus enables a longer replacement interval |
| Deposit control in engine | Prevents forming of sludge and deposits in the engine, which enables a longer engine life |
| Excellent low temperature performance | It provides good lubrication when starting the engine at low temperatures |

Specification:

- API SN/CF;
- ACEA A3/B4;
- MB 229.1;
- VW 501 01/505 00

Typical characteristics

| Characteristics | Method | NISOTEC AUTOLINE PS SAE 10W-40 |
|--|-------------|-----------------------------------|
| SAE Viscosity grade | SAE J300 | 10W-40 |
| Kinematic viscosity at 100°C, mm ² /s | ISO 3104 | 14,5 |
| Viscosity Index | ISO 2909 | 150 |
| Total Base Number TBN, mg KOH/g | ISO 3771 | 10,0 |
| Sulfate ash, m/m % | ISO 3987 | 1,3 |
| Pour Point, °C | ISO 3016 | -33 |
| Flash Point (COC), °C | EN ISO 2592 | 220 |
| Density at 15°C, kg/m ³ | EN ISO 3675 | 874 |

Health, Safety and Environment

Information on the safe handling, storage and disposal of the product, as well as information on precautionary measures and potential hazards, effects on human health and the environment can be found in the Product Safety Data Sheet (SDS). Store the product in its original packaging protected from atmospheric influences. Shelf life 5 years from the date of manufacture.

Available packaging



1L



4L



60L



205L



1000L