

NISOTEC KALOL 22

NISOTEC KALOL 22 is a top-quality hardening oil. Specially formulated to ensure good tempering and elimination of the appearance of cracks and deformations during metal processing by tempering. It provides excellent long-term performance in quenching operations to adjust the hardness and strength of the metal. Excellent economy with a long shelf life due to low volatility and good aging resistance.

Applications:

- Hardening process in open and closed systems where no subsequent washing of parts with water is required
- Recommended for hardening all types of steel: steel for cementation, steel for ball bearings, Mn-Si steel for springs, unalloyed steel.

Characteristics	Advantages
High flash point	Reduced fire risk
Low volatility	Reduced evaporation losses and improved operating conditions
Good thermal and oxidation stability	Longer oil life at elevated system temperatures and less downtime due to maintenance needs

Specification:

- ISO 6743-14 (L-UH)

Typical characteristics

Characteristics	Method	NISOTEC KALOL 22
Kinematic viscosity at 40°C, mm ² /s	ISO 3104	22
Viscosity index	ISO 2909	101
Flash Point (COC), °C	EN ISO 2592	200
Pour Point, °C	ISO 3016	-12
Density at 15°C, kg/m ³	EN ISO 3675	864

Health, Safety and Environment

Information on the safe handling, storage and disposal of the product, as well as information on precautionary measures and potential hazards, effects on human health and the environment can be found in the Product Safety Data Sheet (SDS). Store the product in its original packaging protected from atmospheric influences. Shelf life 5 years from the date of manufacture.

Available packaging



205L



1000L