

NISOTEC MOTOR OIL SF SAE 15W-40



Engine oil



Mineral



Anticorrosive properties



Multigrade

NISOTEC MOTOR OIL SF SAE 15W-40 is a multigrade engine oil designed to provide protection and good performance of older, primarily gasoline engines of classic construction. It is formulated using additives that provide good anti-corrosion protection as well as wear control, thus extending the engine's service life.

Applications:



- Passenger cars, light trucks
- Older, primarily gasoline, engines of classic designs that require oil according to the API SF specification

Characteristics	Advantages
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Thermal and oxidation stability	Helps to resist oil aging
Excellent anti-corrosion properties	Effectively protects all moving parts of the engine from corrosion, thus extending the engine's service life

Specification:

- API SF/CC

Typical characteristics

Characteristics	Method	NISOTEC MOTOR OIL SF SAE 15W-40
SAE Viscosity grade	SAE J300	15W-40
Kinematic viscosity at 100°C, mm ² /s	ISO 3104	14,7
Viscosity Index	ISO 2909	134
Total Base Number TBN, mg KOH/g	ISO 3771	6,0
Pour Point, °C	ISO 3016	-27
Flash Point (COC), °C	EN ISO 2592	225
Density at 15°C, kg/m ³	EN ISO 3675	880

Health, Safety and Environment

Information on the safe handling, storage and disposal of the product, as well as information on precautionary measures and potential hazards, effects on human health and the environment can be found in the Product Safety Data Sheet (SDS). Store the product in its original packaging protected from atmospheric influences. Shelf life 5 years from the date of manufacture.

Available packaging



1L

4L

205L

1000L