

NISOTEC SUPER SAE 15W-40



Engine oil



Turbocharged engines



Euro II/I



Mineral



Multigrade

NISOTEC SUPER SAE 15W-40 is a multigrade engine oil intended for the lubrication of diesel engines of commercial vehicles and various off-road machinery. It is designed for the lubrication of older four-stroke diesel engines, of classic construction, which can also use fuel with an increased sulfur content. It is formulated with base oils and a quality additive package, which ensures improved anti-corrosion protection of the engine, control of the formation of deposits and soot.

Applications:



- Four-stroke diesel engines with and without turbochargers, requiring API CF-4 performance oil and meeting Euro II/I emissions requirements.
- Commercial vehicles and various off-road machinery

Characteristics	Advantages
Wear protection	A permanent oil film provides protection against wear in all operating conditions, which enables a long engine life
Control of deposits in the engine	Prevents the formation of deposits and sludge in the engine, which enables a longer engine life
Stable viscosity	The protective oil film, stable throughout the application period, ensures a stable viscosity within the gradation

Specification:

- API CF-4/SF;
- ACEA E2;
- MB 228.1;
- MAN 271;

Typical characteristics

Characteristics	Method	NISOTEC SUPER SAE 15W-40
SAE Viscosity grade	SAE J300	15W-40
Kinematic viscosity at 100°C, mm ² /s	ISO 3104	14,5
Viscosity Index	ISO 2909	135
Total Base Number TBN, mg KOH/g	ISO 3771	9,5
Pour Point, °C	ISO 3016	-30
Flash Point (COC), °C	EN ISO 2592	220
Density at 15°C, kg/m ³	EN ISO 3675	881

Health, Safety and Environment

Information on the safe handling, storage and disposal of the product, as well as information on precautionary measures and potential hazards, effects on human health and the environment can be found in the Product Safety Data Sheet (SDS). Store the product in its original packaging protected from atmospheric influences. Shelf life 5 years from the date of manufacture.

Available packaging

