

NISOTEC UNIVERSAL SAE 15W-40



Engine oil



Mineral



Excellent protection of high mileage engines



Gasoline and diesel engines



Multigrade

NISOTEC UNIVERSAL SAE 15W-40 is a high-performance universal engine oil for gasoline and diesel engines of passenger vehicles, designed to provide a high level of engine protection and performance. It is formulated using a quality additive system that provides excellent resistance to lubricant degradation caused by high-temperature oxidation and good wear control, thus extending the engine's service life.

Applications:



- Passenger cars, light trucks
- Older gasoline and diesel engines without diesel particulate filters (DPF) requiring oil with API SG/CD standards

Characteristics	Advantages
Multi-purpose application	High quality formulation suitable for various types of older vehicle engines that require excellent product quality
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Improved thermal and oxidation stability	Helps to resist oil aging allowing extended drain interval protection
Deposit control	Prevents forming of sludge and deposits in the engine, which enables a longer engine life

Specification:

- API SG/CD

Typical characteristics

Characteristics	Method	NISOTEC UNIVERSAL SAE 15W-40
SAE Viscosity grade	SAE J300	15W-40
Kinematic viscosity at 100°C, mm ² /s	ISO 3104	14,8
Viscosity Index	ISO 2909	136
Total Base Number TBN, mg KOH/g	ISO 3771	7,5
Pour Point, °C	ISO 3016	-30
Flash Point (COC), °C	EN ISO 2592	224
Density at 15°C, kg/m ³	EN ISO 3675	882

Health, Safety and Environment

Information on the safe handling, storage and disposal of the product, as well as information on precautionary measures and potential hazards, effects on human health and the environment can be found in the Product Safety Data Sheet (SDS). Store the product in its original packaging protected from atmospheric influences. Shelf life 5 years from the date of manufacture.

Available packaging



1L



4L



10L



60L



205L



1000L