

NISOTEC UNIVERSAL SAE 20W-50



Engine oil



Mineral



Excellent protection of high mileage engines



Gasoline and diesel engines



Multigrade

NISOTEC UNIVERSAL SAE 20W-50 is a universal engine oil, for gasoline and diesel engines of passenger vehicles, designed to provide protection and good performance of older engines of classic designs that work in conditions of high external temperatures or have increased oil consumption. It is formulated using a quality additive system that provides excellent resistance to lubricant degradation caused by high-temperature oxidation and good wear control, thus extending the engine's service life.

Applications:



- Passenger cars, light trucks
- Older gasoline and diesel engines without diesel particulate filters (DPF) requiring oil with API SG/CD standards

Characteristics	Advantages
Multi-purpose application	High quality formulation suitable for various types of older vehicle engines that require excellent product quality
Wear protection	Strong oil film provides protection against wear
Thermal and oxidation stability	Helps to resist oil aging
Deposit control	Prevents forming of sludge and deposits in the engine, which enables a longer engine life

Specification:

- API SG/CD

Typical characteristics

Characteristics	Method	NISOTEC UNIVERSAL SAE 20W-50
SAE Viscosity grade	SAE J300	20W-50
Kinematic viscosity at 100°C, mm ² /s	ISO 3104	18,2
Viscosity Index	ISO 2909	130
Total Base Number TBN, mg KOH/g	ISO 3771	7,5
Pour Point, °C	ISO 3016	-27
Flash Point (COC), °C	EN ISO 2592	228
Density at 15°C, kg/m ³	EN ISO 3675	887

Health, Safety and Environment

Information on the safe handling, storage and disposal of the product, as well as information on precautionary measures and potential hazards, effects on human health and the environment can be found in the Product Safety Data Sheet (SDS). Store the product in its original packaging protected from atmospheric influences. Shelf life 5 years from the date of manufacture.

Available packaging



1L



4L



10L



60L



205L



1000L